

Since 1910

DANUSER



U.S. Patent No.: 6,419,245 B1

AUGER CART

G20/40



8800



8900



24" maximum auger diameter

use on any level surface

parking brake

4 wheels and steering capabilities

PACKED FOR  SHIPPING

CONTACT DANUSER

Phone: (573) 642-2246

Fax: (573) 642-2240

E-mail: sales@danuser.com

Web: www.danuser.com

DANUSER AUGER CART

U.S. Patent No.: 6,419,245 B1



Quickly and easily attach/detach, transport, and store
Danuser 3-pt. Hitch Diggers: F8 (shown), G20/40, 8800, and 8900.



Step 1:

Move the Auger Cart into position,
and slowly lower the auger point
into the auger point holder.



Step 2:

Attach the four ratchet straps, and
disconnect the driveline or hydraulic
hoses. Support the digger yoke with
the yoke support assembly.



Step 3:

Disconnect the digger from
the tractor 3-pt. hitch.



Step 4:

Back the Auger Cart away
from the tractor.

See Auger Cart Owner's Manual for complete operation instructions.

Note: Ratchet strap placement is different on Danuser Digger Models G20/40, 8800, and 8900.

Since 1910

DANUSER

500 East Third Street
Fulton, MO 65251-0368

Packed for
ground shipping.

