



573.642.2246 danuser.com/oem


KLIK PINS


All Danuser Klik Pins are forged from high carbon steel and heat treated (core hardened) to withstand wear. Danuser Klik Pins are available in 3/16, 1/4, 5/16, and 7/16 x 11/32 inch pin diameters and are available with or without chain and cotter. The spring steel snap ring is assembled mechanically to prevent any stretch or loss of tension. All parts are zinc plated with the exception of the Danuser Special Duty Klik Pin that has an extra heavy chrome-silicon spring steel snap ring with black oxide finish. The Special Duty Klik Pin requires approximately four times greater force to open than required on other Danuser Klik Pins. The Danuser Safety Lock is the ultimate in a positive quick-release Klik Pin. In the closed position, the free ends of the snap ring are seated in locking grooves. Only a firm pressure to BOTH sides of the snap ring will free the ends from the locking grooves.

		DIMENSIC	ONS IN INCHES			
PART PIN ID SIZE		PIN INSIDE LENGTH RING DIA A B		CHAIN LENGTH C	COTTER SIZE D	
		ROL	JND PINS			
7637	3/16	1-1/4	1	-	-	
7652	3/16	1-1/4	1	6-1/4	3/32 x 3/4	
1185	1/4	1-3/4	1-5/8	-	-	
1600	1/4	1-3/4	1-3/8	-	-	
1601	1/4	1-3/4	1-3/8	7-3/4	3/16 x 3/4	
34072	5/16	2-11/32	2-1/16	-	-	
7618	5/16	2-11/32	1-5/8	-	-	
7619	5/16	2-11/32	1-5/8	7-3/4	3/16 x 3/4	
		FLAT	BACK PINS		1	
317	7/16 X 11/32	1-3/4	1-3/8	7-3/4	3/16 x 3/4	
1533	7/16 X 11/32	1-3/4	1-3/8	-	-	
948	7/16 X 11/32	1-3/4	1-5/8	-	-	
7524	7/16 X 11/32	2	1-7/8	-	-	
7525	7/16 X 11/32	2	1-7/8	7-3/4	3/16 x 3/4	
34046	7/16 X 11/32	2	2-1/16	-	-	
		SPECIA	L DUTY PINS			
7631	7/16 X 11/32	1-3/4	1-3/8	-	-	
7634	7/16 X 11/32	1-3/4	1-3/8	7-3/4	3/16 x 3/4	
7842	7/16 X 11/32	1-3/4	1-5/8	-	-	
7843	7/16 X 11/32	1-3/4	1-5/8	7-3/4	3/16 x 3/4	
7862	7/16 X 11/32	2	1-5/8	-	-	
		SAFET	Y LOCK PINS	·		
9655	7/16 X 11/32	2	1-3/4	7-3/4	3/16 x 3/4	
9656	7/16 X 11/32	2	1-3/4	-	-	









LINK PINS

Danuser Link Pins are forged from medium carbon or alloy steel in pin diameters of 5/8, 7/8, and 1-1/8 inches. Link Pins, cross drilled to accept Danuser Klik Pins, are heat treated and zinc plated to resist rust. Hexagon nuts and spring type lock washers can be purchased for each of the Link Pins. Danuser welcomes your inquiries on machined pins made to your design and specifications.

	PART	DIMENSIONS IN INCHES									
CAT.	ID	Α	В	С	D	E	F	G			
0	5873	5/8	1.44	1.50	.56	.38	.28	5/8-11			
I	5412	7/8	2.00	2.12	.94	.44	.47	7/8-14			
П	5414	1-1/8	1.95	2.12	.94	.44	.47	7/8-14			
111	5866	1-7/16	2.06	2.50	.94	.50	.47	1-1/8-12			

